



XE320Cp

BENEFITS



Ergonomic: the lighter machine of the market



Robust & reliable



Affordable



TO COMPLETE THE PACK



Custom bases and column for benchtop applications in custo

Different size of feet depending on the applications in custo

**3D-Stylus 60°
3D-Stylus 90°
3D-Stylus 120°**

*Ref. 77021

77022

77023*

**Stylus
PN22
PN21**

S52 (available with a shorten foot in custom)

Réf. Spare parts

TECHNICAL SPECIFICATIONS

XE320 Cp

Electrical Supply	110 - 230 V AC
Power	120 VA
Power supply	110 - 230 V AC - 50/60 Hz
Compressed air supply	Nominal Operating Pressure 6 (87.023 PSI), 6.5 Bar (94.275 PSI) maximum
Operating temperature	5 – 45 °C
Operating mode	Independent and with PC
Marking field	
Marking field	50mm X 20mm
Height of Characters	From 0.5 mm to 44.9 mm
Marking Possibilities	Fixed Text/variable ; Dates ; Counters ; DataMatrix ; Logos
Font	Continuous dot or dot per dot
Interface	
Connections	USB / Ethernet /Dedicated or Standard Inputs-Outputs
Keyboard	External keyboard
Driving	Software T05
CARACTERISTIQUES PHYSIQUE	
Weight	2.7 kg

